

DRUM SCREEN SM 720.2 SA



DIMENSIONS

Chassis	Semi-trailer
Total weight (kg)	24000
Length (mm)	17000
Width (mm)	6900
Height (mm)	4000
Transport width (mm)	2550
Transport height (mm)	4000
Transport length (mm)	13350

DRIVE

Engine type	diesel engine
Marke	Deutz TCD 3.6 L4
Exhaust level	Stage V / Tier 4f
Motor power (kW / PS)	85 / 116 (at 1800 rpm)
Fuel tank (l)	400
Torque (Nm)	max. 480 at 1600 rpm

DISCHARGE CONVEYOR

Width (mm)	1000
Length (mm)	5500 (3000*) *option
Belt speed (m/s)	1,6
Height (mm)	3500

DISCHARGE CONVEYOR SIDE

Width (mm)	1000
Length (mm)	5500
Belt speed (m/s)	3,1
Height (mm)	3500

SCREEN DRUM

Diameter (mm)	2000
Length (mm)	7100
Mesh size (mm)	selectable, 3 - 150 mm
Mesh type	selectable
Drum wall thickness (mm)	selectable
Drum speed (min-1)	0-24
Screening area (m ²)	38,8

Applications

Like all Doppstadt SM machines the SM 720.2 SA happily accepts waste and raw materials of all types for screening. It is equally suitable for compost, earths, light construction waste, wood, biomass, sand, and gravel.



Advantages

- Maximum throughput capacity at high- quality screening results due to extra large screening area
- Many options to meet various requirements
- Large size feeding hopper and extra long output conveyors allow feeding of the machine with large front loaders
- Low operation costs due to powerful drive at low fuel consumption, short set-up time
- Unique load sensing feeder control makes sure that the capacity of the machine is used at the optimum in safe operation without interruption.
- Extensive standard safety equipment (e.g. intrusion protection, emergency stop, machine monitoring)
- European road approval