

LETTO

ASPHALT CONTAINER

ASPHALT CONTAINER

AF17
AF17/2K

FM

ASPHALT CONTAINER

Asphalt container for road maintenance



The OLETTO asphalt container is the perfect solution in modern road maintenance. The hotbox keeps the asphalt hot all day, and is the ideal pothole patcher for repairing asphalt surfaces after laying pipelines, or any other job where you have to patch with small amounts of asphalt.

The advantages of the hotbox are many such as warm asphalt all day, reduced wage costs, by processing easier and much faster, fully automatic temperature control and a hydraulic auger for easy unloading.

The OLETTO thermo asphalt container consists of two separate heating chambers. The chambers are insulated with Rockwool which prevent the asphalt from cooling, and is equipped with new technology including a gas saving system in both chambers.
A HARDOX auger with geared drive leads the asphalt out through a chute to the desired place for repair. The auger is hydraulic driven either by using the hydraulic of the truck or an integrated hydraulic station driven by a gas- or diesel engine.









TECHNICAL SPECIFICATIONS

	AF17	AF17/2K
Chambers	1	1
Thermometer	Digital	Digital
Temperature regulation	Automatic	Automatic
Burner type	Lamella	Lamella
Max. volume	0,8 m³	0,8 m³
Max capacity	1,7 t	1,7 t
Weight basic model	650 kg	700 kg
Gas consumption	0,5 kg/h	0,5 kg/h
Standard colour	RAL1007	RAL1007
Insulation	50 mm Rockwool	50 mm Rockwool
Gas pressure	0,75 bar	0,75 bar
Dimension mm	1500 x 1650 x 1130	

FM - Simpler, with few spareparts

© FM 2011. Ret til ændringer forbeholdes

FM MASKINER A/S
Kirkevej 6, DK-6621 Gesten

Tel. +45 7555 7022, Fax +45 7555 7500
www.fm-maskiner.dk